5% AXIAL LEADED RESISTOR

BRN BLK GRN GLD

1 0 5

VALUE 1.0M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____105

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

RED RED GRN GLD

2 2 5

VALUE 2.2M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____225

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

ORN VIO GRN GLD

4 7 5

VALUE 47k Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____475

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

BRN BRN GRN GLD

1 1 5

VALUE 1.1M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____115

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

RED YEL GRN GLD

2 4 5

VALUE 2.4M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____245

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

GRN BRN GRN GLD

5 1 5

VALUE 5.1M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____515

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

BRN RED GRN GLD

1 2 5

VALUE 1.2M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____125

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

RED VIO GRN GLD

2 7 5

VALUE 2.7M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____275

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

GRN BLU GRN GLD

5 6 5

VALUE 5.6M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____565

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

BRN ORN GRN GLD

1 3 5

VALUE 1.3M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____135

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

ORN BLK GRN GLD

3 0 5

VALUE 3.0M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____305

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

BLU RED GRN GLD

6 2 5

VALUE 6.2M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____625

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

BRN GRN GRN GLD

1 5 5

VALUE 1.5M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____155

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

ORN ORN GRN GLD

3 3 5

VALUE 3.3M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____335

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

BLU GRY GRN GLD

6 8 5

VALUE 6.8M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____685

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

BRN BLU GRN GLD

1 6 5

VALUE 1.6M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____165

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

ORN BLU GRN GLD

3 6 5

VALUE 3.6M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____365

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

VIO GRN GRN GLD

7 5 5

VALUE 7.5M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____755

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

BRN GRY GRN GLD

1 8 5

VALUE 1.8M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____185

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

ORN WHT GRN GLD

3 9 5

VALUE 3.9M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____395

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

GRY RED GRN GLD

8 2 5

VALUE 8.2M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____825

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

RED BLK GRN GLD

2 0 5

VALUE 2.0M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____205

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

YEL ORN GRN GLD

4 3 5

VALUE 4.3M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____435

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____

5% AXIAL LEADED RESISTOR

WHT BRN GRN GLD

9 1 5

VALUE 9.1M Ω

POWER 250mW

TOLERANCE ±5%

IN HOUSE P/N: _____915

TYPE: Carbon Film

MAX VOLTAGE: 250 VDC

VENDOR & P/N: _____